

Corporate Headquarters 400 Valley Road Warrington, PA 18976 1-800-523-2575 FAX 1-800-343-3291 Email: info@ polysciences.com www.polysciences.com Europe - Germany Polysciences Europe GmbH Handelsstr. 3 D-69214 Eppelheim, Germany (49) 6221-765767 FAX (49) 6221-764620 Email: info@ polysciences.de

# TECHNICAL DATA SHEET 320

Page 1 of 1

# Ruthenium Tetroxide

0.5% Aqueous Solution

#### **Background and Properties:**

In its crystal form, ruthenium (VIII) oxide ( $RuO_4$ ), m.w. 165.7, is a golden yellow, volatile solid which sublimes at room temperature. It has mp of  $25.4^{\circ}C$  and bp of  $40^{\circ}C$ . It is sparingly soluble in water (2% w/v at  $20^{\circ}C$ ), but freely soluble in carbon tetrachloride. Solvents such as ether, alcohol, benzene and pyridine react violently with  $RuO_4$ . Ruthenium tetroxide is not only less volatile and less toxic¹ than osmium tetroxide but it is also a stronger oxidizing agent.  $^{1.3}$  It reacts with many organic compounds like olefins, sulfides, primary and secondary alcohols, and aldehydes. It also degrades benzene rings.  $^3$ 

## **Applications and Instructions:**

Ruthenium tetroxide is closely related to osmium tetroxide and is useful as a staining agent for Electron Microscopy of polymers and their blends, and as a fixative for biological samples. 46 It fixes the membranes in rat kidneys, liver, and ventral lobe of prostate, and these membranes appeared thicker than those preserved with other fixatives. 7 Ruthenium tetroxide shows excellent staining of saturated and unsaturated polymer materials with improved image contrast. RuO<sub>4</sub> staining also has a stabilizing effect against electron beam damage of material films. Ruthenium tetroxide penetrates tissue very slowly, reacting strongly with proteins, glycogen, and monosaccharides. 7.8

A typical procedure consists of prefixing with buffered 4% glutaraldehyde followed by postfixation with buffered ruthenium tetroxide  $0.1 \cdot .05\%$  at pH = 7.1 for 1 hour at  $4^{\circ}$ C. <sup>5</sup> Specimens should be rinsed in water before dehydrating with alcohol or acetone.

**NOTE:** Ruthenium tetroxide, 0.5% aqueous, is a light golden brown solution. Solutions will turn black with exposure to organic material or strong U.V. light.

#### **Handling Precautions:**

Ruthenium tetroxide is a strong oxidizing agent and must be stored, refrigerated, protected from light. It reacts violently with filter paper and alcohol. Do not place ruthenium tetroxide solutions into waste containers containing alcohol, ether, benzene, pyridine, or other organic compounds.

Ruthenium tetroxide has an acrid odor. Vapors are irritating to eyes and respiratory tract. Wear protective goggles and gloves. Handle only in a hood. In case of spillage, flush with sodium bisulfite solution to decompose  $RuO_4$  and then flush with plenty of water.

### **Ordering Information:**

Cat. #	Description	Size
18253	Ruthenium tetroxide,	5 x 10ml
	0.5% stabilized aqueous solution	10 ×10 ml
	·	$25 \times 10 \text{ m}$

\* supplied in ampoules

To Order:

In The U.S. Call: 1-800-523-2575 • 215-343-6484 In The U.S. FAX: 1-800-343-3291 • 215-343-0214

In Germany Call: (49) 6221-765767 In Germany FAX: (49) 6221-764620

Order online anytime at www.polysciences.com

#### **References:**

- Berkowitz, L.M. and Rylander, P.N., J. Am. Chem. Soc., 80, 6682 (1958).
- 2. Djerassi, C. and Engle, R.R., J. Am. Chem. Soc., **75**, 3838 (1953).
- 3. Wolfe, S., Hasan, S.K., and Campbell, J.R., Chem. Comm., 1420 (1970).
- 4. Trent, J.S., Macromolecules, 17, 2930 (1984); 16, 539 (1983).
- 5. Peltarri, A., Histochem. J., 11, 599 (1979).
- Caughey, R.C. and Miller, M.A., Proceed. of 44th Ann. Mtg. EMSA (1986), p. 256.
- 7. Hayat, M.A., Fixation for Electron Microscopy, Academic Press, NY, 1981, p. 194.
- 8. Gaylarde, P., Science, 161, 1157 (1968).

Should any of our materials fail to perform to our specifications, we will be pleased to provide replacements or return the purchase price. We solicit your inquiries concerning all needs for life sciences work. The information given in this bulletin is to the best of our knowledge accurate, but no warranty is expressed or implied. It is the user's responsibility to determine the suitability for his own use of the products described herein, and since conditions of use are beyond our control, we disclaim all liability with respect to the use of any material supplied by us. Nothing contained herein shall be construed as a recommendation to use any product or to practice any process in violation of any law or any government regulation.